



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷:

H04M 1/72, 1/02

A1

(11) International Publication Number:

WO 00/01133

(43) International Publication Date:

6 January 2000 (06.01.00)

(21) International Application Number: PCT/US99/09774

(22) International Filing Date: 5 May 1999 (05.05.99)

(30) Priority Data:

09/107,726

30 June 1998 (30.06.98)

US

(71) Applicant: ERICSSON INC. [US/US]; 7001 Development Drive, Research Triangle Park, NC 27709 (US).

(72) Inventor: MURRAY, Matthew, Justin; Apartment L, 3021 Walnut Creek Parkway, Raleigh, NC 27606 (US).

(74) Agent: MONCO, Dean, A.; Wood, Phillips, VanSanten, Clark & Mortimer, Suite 3800, 500 West Madison Street, Chicago, IL 60661-2511 (US).

(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).


Published

With international search report.

(54) Title: METHOD AND APPARATUS FOR CONTROLLING A PERFORMANCE CHARACTERISTIC OF AN ELECTRONIC DEVICE

(57) Abstract

A method and apparatus are provided for controlling a performance characteristic of an electronic device. In one form, the electronic device includes a frame, a first subassembly on the frame and including a component encoded with a measured value of a first performance characteristic of the first subassembly, a download circuit on the frame to download the measured value from the encoded component, and an electronic circuit on the frame to a) receive a signal from the download circuit representative of the measured value and b) control a second performance characteristic of the electronic device as a function of the signal. In one form, the method includes the steps of measuring a value of a first performance characteristic of a first subassembly of an electronic device, encoding a component with the value, assembling the first subassembly to the electronic device, downloading the value from the component, and controlling a second performance characteristic of the electronic device as a function of the downloaded value.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

- 1 -

METHOD AND APPARATUS FOR CONTROLLING A PERFORMANCE CHARACTERISTIC OF AN ELECTRONIC DEVICE

FIELD OF THE INVENTION

This invention relates to electronic devices, and more particularly, to
5 electronic devices, such as mobile phones, having a performance characteristic,
such as a transmission gain, which has a selectable optimal performance range or
value.

BACKGROUND OF THE INVENTION

It is common for electronic devices to have one or more performance
10 characteristics which have a desired performance range or value. For example, it
is often desirable to control the transmission gain of the speech or audio signal of
mobile phones within a predetermined range to provide an acoustic level for the
transmission path that is acceptable for the intended operating environment of the
mobile phones. The performance range or value of the transmission gain can be
15 particularly critical to the actual and perceived performance of the mobile phone in
urban areas having relatively high levels of background noise.

In mobile phones employing a flip that includes a passive acoustic
channel or a transducer, such as a microphone, the transmission gain is a function
of both the transmitter circuitry in the main housing of the mobile phone and the
20 sensitivity level of the transducer and associated circuitry in the flip or, in the case
of an acoustic channel, the mechanical seal of the acoustic channel and the
absence of obstructions in the channel. One approach to obtaining the desired
performance range for the transmission gain in such mobile phones is to preset the
gain circuitry of the phones to a level that assumes nominal values for the sensitivity
25 levels of the electronic components, such as the microphone, in the transmission
path or, in the case of an acoustic channel, the nominal value for the acoustic gain
of the acoustic channel. However, this approach does not address variations in the

- 2 -

sensitivity levels or acoustic gain from one component to the next component, which can result in a transmission gain of the speech signal that varies by up to 6dB from one mobile phone to the next. Another approach is to set the transmission gain by performing audio transmission level trim after the flip has been mounted to the remainder of the mobile phone. However, this approach may increase the cost and complexity of assembling such phones.

SUMMARY OF THE INVENTION

In accordance with the present invention, an electronic device includes a frame, a first subassembly on the frame and including a component encoded with a measured value of a first performance characteristic of the first subassembly, a download circuit on the frame to download the measured value from the encoded component, and an electronic circuit on the frame to a) receive a signal from the download circuit representative of the measured value and b) control a second performance characteristic of the electronic device as a function of the signal.

In one form, the first performance characteristic is different from the second performance characteristic.

In one form, the electronic device further includes a transmitter on the frame. The first subassembly includes a transducer circuit operably associated with the transmitter. The measured value is the sensitivity level of the transducer circuit, and the second performance characteristic is a transmission gain through the transmitter and the transducer circuit.

In one form, the electronic device further includes a transmitter on the frame. The first subassembly includes an acoustic channel operably associated with the transmitter. The measured value is the acoustic gain of the acoustic channel, and the second performance characteristic is a transmission gain through the transmitter and the acoustic channel.

In accordance with one form of the present invention, a mobile phone includes a frame; a transmitter on the frame; a flip assembly on the frame and

- 3 -

including a transducer circuit operably associated with the transmitter, and a component encoded with a measured value of a sensitivity level of the transducer circuit; a download circuit on the frame to download the measured value from the encoded component; and an electronic circuit on the frame to a) receive a signal
5 from the download circuit representative of the measured value and b) control a transmission gain through the transmitter and the transducer circuit as a function of the signal.

In accordance with one form of the present invention, a mobile phone includes a frame; a transmitter on the frame; a flip assembly on the frame and
10 including an acoustic channel operably associated with the transmitter, and a component encoded with a measured value of an acoustic gain of the acoustic channel; a download circuit on the frame to download the measured value from the encoded component; and an electronic circuit on the frame to a) receive a signal from the download circuit representative of the measured value and b) control a
15 transmission gain through the transmitter and the transducer circuit as a function of the signal.

In one form, the electronic circuit controls the second performance characteristic of the electronic device within a desired performance range as a function of the signal.

20 In one form, the encoded component includes a magnetic strip, and the download circuit includes a magnetic strip reader.

In one form, the encoded component includes a bar code, and the download circuit includes a bar code scanner.

In one form, the encoded component includes a memory chip, and the
25 download circuit includes circuitry to access the memory chip to download the encoded value from the memory chip.

In accordance with one form of the present invention, a method is provided for setting a performance characteristic of an electronic device within a desired performance range. The method includes the steps of measuring a value

- 4 -

of a first performance characteristic of a first subassembly of an electronic device, encoding a component with the value, assembling the first subassembly to the electronic device, downloading the value from the component, and controlling a second performance characteristic of the electronic device within a desired performance range as a function of the downloaded value.

In one form, the controlling step includes controlling the second performance characteristic of the electronic device within a desired performance range as a function of the downloaded value.

In one form of the invention, the encoding step includes encoding a component on the first subassembly with the value.

In one form of the invention the downloading step occurs after the assembling step.

In one form of the invention the downloading step precedes the assembling step.

In one form, the downloading step includes the step of powering on the electronic device.

In accordance with one form of the present invention, a method is provided for setting a transmission gain of a mobile phone including a main housing, a transmitter on the housing, and a flip. The flip includes a transducer circuit. The method includes the steps of measuring a value of a sensitivity level of the transducer circuit in the flip, encoding the value in a component on the flip, assembling the flip onto the main housing, downloading the value from the component, and controlling a transmission gain of the mobile phone as a function of the downloaded value.

In accordance with one form of the present invention, a method is provided for sending the transmission gain of the mobile phone in the main housing, transmitter on the housing, and a flip. The flip includes an acoustic channel. The method includes the steps of measuring a value of an acoustic gain of the acoustic channel and flip, encoding the value in a component on the flip, assembling the flip

- 5 -

onto the main housing, downloading the value from the component, and controlling a transmission gain of the mobile phone as a function of the downloaded value.

In one form, the downloading step includes the step of powering on the mobile phone.

5 BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a diagrammatic plan view of an electronic device in the form of a mobile phone embodying the present invention;

Fig 2 is a diagrammatic plan view of another mobile phone embodying the present invention; and

10 Fig. 3 is a flow chart illustrating a method embodying the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

15 An exemplary embodiment of an electronic device 10, made according to the invention, is described herein and illustrated in the drawings in the form of a mobile cellular phone 10. However, it should be understood that the invention may find utility in other applications and is not limited to use in a mobile cellular telephone.

20 With reference to Fig. 1, the mobile phone 10 includes a frame in the form of a main housing 12, a first subassembly in the form of a flip 14 pivotably mounted on the housing 12 by a hinge 16, and a transmitter, shown generally at 18, mounted on the housing 12. The flip 14 includes a transducer circuit, shown generally at 20, which in turn includes a transducer in the form of a microphone 22. The flip 14 also includes a component 24 associated with, and preferably mounted
25 on, the flip 14 and encoded with a measured value of a first performance characteristic in the form of the sensitivity level of the transducer circuit 20 of the flip 14.

- 6 -

The phone 10 further includes a download circuit 26 mounted on the housing 12 to download the value from the encoded component 24, and an electronic circuit, shown generally at 28, mounted on the housing 12 to a) receive a signal 30 from the download circuit 26 representative of the downloaded value and
5 b) control a second performance characteristic in the form of the transmission gain of the phone 10 within a desired performance range or value as a function of the signal 30.

Many types of encoded components 24 and download circuits 26 are well known in the art and may be utilized to practice the invention. For example, in
10 one embodiment of the invention, the encoded component 24 includes a magnetic strip encoded with the measured value of the sensitivity of the flip 14 level and the download circuit 26 includes a magnetic strip reader. By way of further example, in another embodiment of the invention, the encoded component 24 includes a memory chip encoded with the measured value of the sensitivity level of the flip 14,
15 and the download circuit 26 includes circuitry for accessing the memory chip to download the measured value from the memory chip.

Preferably, the electronic circuit 28 is provided in the form of programmable gain control circuitry, which is well known in the art. However, any type of electronic circuit 28 that can receive a signal 30 and control a second
20 performance characteristic of an electronic device, such as a transmission gain of the phone 10, as a function of the signal 30, may be utilized to practice the invention. Accordingly, a more detailed description of the electronic circuit 28 is not required.

Similarly, because there are many types of housings 12, flips 14,
25 hinges 16, transmitters 18, transducer circuits 20, and transducers 22 that are well known in the art and that may be utilized to practice the invention, a more detailed description of these components is not required.

Fig. 2 shows another embodiment of the invention in the form of a mobile phone that is identical to the mobile phone shown in Fig. 1 except that the

- 7 -

transducer circuitry 20 and transducer 22 are located in the housing 12 rather than in the flip 14, which includes a passive acoustic channel 32 rather than a transducer circuit 20 and transducer 22. The acoustic gain of the flip 14 shown in Fig. 2 is a function of the mechanical seal of the acoustic channel 32 and the absence of
5 obstructions in the channel 32. The encoded component 24 is encoded with a measured value of a first performance characteristic in the form of the acoustic gain of the acoustic channel 32 of the flip 14.

The method of the invention may best be understood with reference to the flow diagram illustrated in Fig. 3. As shown at blocks 40 and 42, the
10 sensitivity level or acoustic gain is measured for the flip 14, and then the measured value of the sensitivity level or acoustic gain is encoded in the component 24 associated with, and preferably on, the flip 14. Next, as shown at blocks 44 and 46, the flip 14 is assembled to the main housing 12 of the phone 10 which includes the transmitter 18 and the electronic circuit 28 with a preset gain level, and the encoded
15 value is downloaded from the component 24. Finally, as shown at block 48, the electronic circuit 28 controls the transmission gain of the phone 10 by either a) maintaining the preset gain level in the phone 10 if the preset gain level provides the desired performance range for the transmission gain based on the downloaded value, or b) if the preset level does not provide the desired performance range for
20 the transmission gain based on the downloaded value, resetting the gain level to achieve the desired performance range.

It is anticipated that the method of the invention will be utilized for the mass production of phones 10. In such mass production, the steps of blocks 40 and 42 may be performed on a plurality of flips 14 prior to the steps of blocks 44, 46, and
25 48 to improve the production efficiency.

According to one preferred embodiment of the method, the assembling step of block 44 precedes the downloading step of block 46, and the downloading step of block 46 includes the step of powering on the phone 10 to initialize the downloading of the encoded value.

- 8 -

According to another embodiment of the invention, the phone 10 does not include a download circuit 26 mounted on the housing 12. Rather, as shown by the phantom in Fig. 1 and Fig. 2, the download circuit 26 is provided in the form of a bar code scanner that may be independent of the phone, and the encoded component 24 includes a bar code encoded with the measured value of the sensitivity level or acoustic gain of the flip 14. With this embodiment of the phone 10, the downloading step of block 46 includes scanning the bar code of the encoded component 10, processing the downloaded value through a programmable computer that may be independent of the phone 10 to determine the appropriate gain level for the phone 10, and uploading a command from the independent computer to the phone 10 that will direct the electronic circuit to provide the appropriate gain level for the phone 10. For this embodiment, the assembling step of block 44 may precede the downloading step of block 46, or the downloading step of block 46 may precede the assembling step of block 44, or the assembling and downloading steps of blocks 44 and 46 may occur essentially simultaneously.

The foregoing disclosure of specific embodiments is intended to be illustrative of the broad concepts comprehended by the invention.

CLAIMS

1. An electronic device comprising:
a frame;
a first subassembly on the frame and comprising a component encoded with
5 a measured value of a first performance characteristic of the first subassembly;
a download circuit on the frame to download the measured value from the
encoded component; and
an electronic circuit on the frame to a) receive a signal from the download
circuit representative of the measured value and b) control a second performance
10 characteristic of the electronic device as a function of the signal.

2. The electronic device of claim 1 wherein the first performance
characteristic is different from the second performance characteristic.

3. The electronic device of claim 1 wherein the electronic circuit on the
frame is configured to control the second performance characteristic of the
15 electronic device within a desired performance range as a function of the signal.

4. The electronic device of claim 1 further comprising a transmitter on the
frame, and wherein the first subassembly comprises a transducer circuit including
a transducer operably associated with the transmitter, the measured value is the
sensitivity level of the transducer circuit, and the second performance characteristic
20 is the transmission gain through the transmitter and the transducer circuit.

5. The electronic device of claim 1 further comprising a transmitter on the
frame, and wherein the first subassembly comprises an acoustic channel and the
measured value is the acoustic gain of the acoustic channel, and the second

- 10 -

performance characteristic is the transmission gain through the transmitter and the acoustic channel.

6. The electronic device of claim 1 wherein the encoded component comprises a magnetic strip, and the download circuit comprises a magnetic strip reader.

7. The electronic device of claim 1 wherein the encoded component comprises a bar code, and the download circuit comprises a bar code scanner.

8. The electronic device of claim 1 wherein the encoded component comprises a memory chip, and the download circuit comprises circuitry to download the encoded value from the memory chip.

9. A mobile phone comprising:
a frame;
a transmitter on the frame;
a flip assembly on the frame and comprising a transducer circuit operably associated with the transmitter, and a component encoded with a measured value of a sensitivity level of the transducer circuit;
a download circuit on the frame to download the measured value from the encoded component; and
an electronic circuit on the frame to a) receive a signal from the download circuit representative of the measured value and b) control a transmission gain through the transmitter and the transducer circuit within a desired performance range as a function of the signal.

- 11 -

10. The electronic device of claim 9 wherein the encoded component comprises a magnetic strip, and the download circuit comprises a magnetic strip reader.

11. The electronic device of claim 9 wherein the encoded component
5 comprises a bar code, and the reader comprises a bar code scanner.

12. The electronic device of claim 9 wherein the encoded component comprises a memory chip, and the download circuit comprises circuitry to download the encoded value from the memory chip.

13. The electronic device of claim 9 wherein the electronic circuit is
10 configured to control the transmission gain through the transmitter and the transducer circuit within a desired performance range as a function of the signal.

- 12 -

14. A mobile phone comprising:

a frame;

a transmitter on the frame;

5 a flip assembly on the frame and comprising an acoustic channel operably associated with the transmitter, and a component encoded with a measured value of an acoustic gain of the acoustic channel;

a download circuit on the frame to download the measured value from the encoded component; and

10 an electronic circuit on the frame to a) receive a signal from the download circuit representative of the measured value and b) control a transmission gain through the transmitter and the acoustic channel within a desired performance range as a function of the signal.

- 13 -

15. A method of setting a performance characteristic of an electronic device within a desired performance range, the method comprising the steps of:

measuring a value of a first performance characteristic of a first subassembly of an electronic device;

- 5 encoding a component with the value ;
 assembling the first subassembly to the electronic device;
 downloading the value from the component; and
 controlling a second performance characteristic of the electronic device as
a function of the downloaded value.

- 10 16. The method of claim 15 wherein the controlling step comprises
controlling the second performance characteristic within a desired range as a
function of the downloaded value.

17. The method of claim 15 wherein the encoding step comprises
encoding a component on the first subassembly with the value.

- 15 18. The method of claim 15 wherein the downloading step precedes the
assembling step.

19. The method of claim 15 wherein the downloading step occurs after the
assembling step.

- 20 20. The method of claim 15 wherein the downloading step further
comprises the step of powering on the electronic device.

- 14 -

21. A method of setting a transmission gain of a mobile phone including a main housing, a transmitter on the housing, and a flip, the flip including a transducer circuit, the method comprising the steps of:

measuring a value of a sensitivity level of the transducer circuit in the flip;

5 encoding a component with the value;

assembling the flip onto the main housing of the electronic device;

downloading the value from the component; and

controlling a transmission gain of the mobile phone as a function of the downloaded value.

10 22. The method of claim 21 wherein the downloading step comprises the step of powering on the mobile phone.

23. The method of claim 21 wherein the encoding step comprises encoding a component on the flip with the value.

15 24. The method of claim 23 wherein the downloading step occurs after the assembling step.

- 15 -

25. A method of setting a transmission gain of a mobile phone including a main housing, a transmitter on the housing, and a flip, the flip including an acoustic channel, the method comprising the steps of:

measuring a value of an acoustic gain of the acoustic channel in the flip;

5 encoding a component with the value;

assembling the flip onto the main housing of the electronic device;

downloading the value from the component; and

controlling a transmission gain of the mobile phone as a function of the downloaded value.

10 26. The method of claim 25 wherein the downloading step comprises the step of powering on the mobile phone.

27. The method of claim 25 wherein the encoding step comprises encoding a component on the flip with the value.

15 28. The method of claim 27 wherein the downloading step occurs after the assembling step.




Fig. 2





Fig. 1

2/2

Fig. 3

INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 99/09774

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 H04M1/72 H04M1/02

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 H04M H04Q

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	DE 41 40 585 A (GRUNDIG EMV) 17 June 1993 (1993-06-17) the whole document	1-28
Y	DE 34 36 696 A (BOSCH GMBH ROBERT) 10 April 1986 (1986-04-10) abstract column 3, line 6 - column 4, line 15 column 5, line 2 - column 7, line 12 figures 1,2	1-28
A	US 5 731 992 A (TORREGROSSA PHILIPPE) 24 March 1998 (1998-03-24) abstract column 1, line 19-38 column 2, line 18 - column 3, line 37 column 4, line 50 - column 6, line 22 figures 5,6	1,9,14, 15,21,25
	--- -/--	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

30 August 1999

Date of mailing of the international search report

06/09/1999

Name and mailing address of the ISA
European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Golzio, D

INTERNATIONAL SEARCH REPORT

Int'l Application No
PCT/US 99/09774

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP 0 420 508 A (NOKIA MOBILE PHONES LTD) 3 April 1991 (1991-04-03) column 1, line 1-20 column 1, line 43 - column 2, line 12 figure 1 ----	1,9,14, 15,21,25
A	EP 0 376 666 A (ASTEC INT LTD) 4 July 1990 (1990-07-04) abstract page 2, line 8-45 page 3, line 20-46 -----	1,9,14, 15,21,25

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 99/09774

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
DE 4140585 A	17-06-1993	AT 154739 T DE 59208631 D EP 0550805 A	15-07-1997 24-07-1997 14-07-1993
DE 3436696 A	10-04-1986	EP 0178393 A JP 1923347 C JP 6052910 B JP 61093759 A	23-04-1986 25-04-1995 06-07-1994 12-05-1986
US 5731992 A	24-03-1998	FR 2720837 A CN 1128355 A EP 0686853 A FI 952708 A	08-12-1995 07-08-1996 13-12-1995 07-12-1995
EP 0420508 A	03-04-1991	FI 83715 B AT 141033 T DE 69027964 D DE 69027964 T US 5423070 A US 5313656 A	30-04-1991 15-08-1996 05-09-1996 06-03-1997 06-06-1995 17-05-1994
EP 0376666 A	04-07-1990	AU 620190 B AU 4708489 A CA 2006159 A CN 1045497 A JP 2265333 A US 5201063 A	13-02-1992 05-07-1990 28-06-1990 19-09-1990 30-10-1990 06-04-1993